

## Reverse Vending Recycling Technology

Envipco's RVM model for return centres with minimal available space and low volume drinks package recycling such as convenience stores, pharmacies, petrol stations, and schools.

## FLEX FEATURES

- Simple, small footprint collection unit
- Industry leading container acceptance speed
- Dual compaction technology
- Available Glass option
- 'Plug and play' – works on standard electric
- Easy cleaning and service
- Front or Rear unload (through wall installation)
- Custom machine graphics and screen interface
- Comprehensive digital marketing options



**PLASTIC & CANS**

**PLASTIC, GLASS & CANS**

# FLEX



**PLASTIC & CANS**

# FLEX SPECIFICATIONS

## Performance

- Up to 45 containers per minute

## Container Size

- Plastic containers up to 3 Litre
- Aluminium cans up to 1 Litre
- Glass bottles up to 1.3 Litre

## Storage Capacity\*

- Dual bins with 60% PET/40% can volume
- Aluminium cans: 650
- Plastic bottles: 320

## Densification

- Patented dual-stage Can/PET flattener

## Container Identification

- Complete 360 ring of barcode readers & shape recognition
- Metal detection
- Weight measurement

## Standard Equipment

- Secure state of the art protocols for accounting data exchange

## Communication and Data Management

- LAN interface (Ethernet TCP/IP)
- Optional cellular modem
- Linux operating system and uninterrupted power supply ensures data integrity
- enVision Portal Remote reporting and maintenance software

## Consumer Interface

- Continuous feed entry port
- High-resolution color LCD touch screen
- High-resolution graphics
- Compliant with accessibility guidelines
- Comprehensive digital marketing, payment and reward options

## Cabinet

- Reliable steel design and durable electrostatic powder coat finish
- Base cabinet with levelers and casters

## Machine

- Dimensions: 1854mm h x 600mm w x 900mm d (73" h x 23.625" w x 35.375" d)
- Footprint: 0.54m<sup>2</sup>
- Weight: approx. 230 kg

## Optional Equipment


- Loyalty card reader
- enVision Portal RVM management (Wifi)
- Audible and visual external alarm system
- Glass soft drop side cabinet 1854mm h x 600mm w x 900mm d (73" h x 23.625" w x 35.375" d)
- Capacity approx. 165 bottles

## Electrical

- Mains US 208-240VAC 1PH 60HZ 20A
- Mains EU 230VAC 1PH 50HZ 16A
- Mains UK 230VAC 1PH 50HZ 13A

## Environment

- -5°C – 35°C (23°F – 95°F)
- Suitable for protected locations



\* Aluminium and Glass assume 355ml (12oz) containers, PET assumes 500ml (16.9oz) containers

Note: Specifications are a guide and for reference, contact your Envipco sales representative for further detailed information.

FLEXREVF04012021