



Self-Checkout Solution

S15

Serve more customers without increasing checkout staff. The S15 is fully customisable with an adaptable design to perfectly fit your stores' layout. Cash, card and mobile payment options mean all your customers will benefit from the enhanced checkout experience however they choose to pay.



More than just hardware, comprehensive software delivers a powerhouse solution guaranteed to deliver. What is holding you back?

| Dimensions (W \times D \times H) | 1488 × 734 × 2104mm |
|--------------------------------------|--|
| (including scale and | |
| side table) | |
| Weight | 110kg (scale: 35kg, side table: 14kg) |
| Power supply | 100-240VAC, 50Hz |
| Current consumption | 7A |
| Operating environment | 0°C to +40°C, 20 to 80% relative humidity, non-condensing |
| Storage environment | -20°C to +70°C, 5 to 90% relative humidity, non-condensing |
| Max. operating altitude | 2000m |
| Material | Steel, aluminum, stainless steel, plastic |
| Protection | IP20, designed for indoor use |
| Panel PC | Processor i3-4330TE, 2.4GHz |
| | SSD 128GB |
| | RAM 4GB |
| | Connectivity: 1 × COM-port (RJ45) with RI / 5V / 12V Selectable, |
| | $3 \times \text{USB } 2.0$, $2 \times \text{USB } 3.0$, $1 \times 24\text{V-powered USB Port}$, |
| | 1 × cash drawer port RJ11 (12V / 24V), 1 × Gigabit LAN Port RJ45, |
| | 2 × video ports |
| | 2 × 2W internal speaker |
| Screen | LCD touch monitor: |
| | 15", 1024 × 768 pixels |
| | Contrast typ. 1000:1 |
| | Brightness typ. 350 nits |
| | Projected capacitive touch |

| Fixed scanner | Type: 2D Optical Resolutions: 5mm (Code 39), 5mm (PDF417), 10mm (Data Matrix), 10mm (QR Code) |
|----------------------------|---|
| Handheld scanner | Type: 2D Optical Resolutions: 5mm (Code 39), 6.6mm (PDF417), 10mm (Data Matrix), 10mm (QR Code) |
| Printer | Technology: Direct thermal line printing, black/white, 250mm/s Resolution: 203 × 203DPl or 203 × 180DPl Max. paper roll diameter: 83mm; 60gm < grammage <140gm End-of-roll sensor |
| Scale (optional) | 460 581mm 80 kg max, accuracy 10g |
| Cash management (optional) | GLORY CI-10 Family |
| Semaphore | LED illumination, different colors selectable |
| Side table (optional) | 460 × 560mm 14 kg |
| Safety certifications | EN60950-1 |
| EMC, EMI certifications | EN62311, EN55022 class A, EN52024, EN61000 CISPR 24 / EN 55024, CISPR 32 / EN 55032 class A, EN 61000-3-2, EN 61000-3-3 |

^{*}Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-10

Compact cash recycling solution, enabling automated cash handling at point-of-sale positions.



CI-100

Fast secure cash processing and storage in the back office.



Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

☎ +44 (0)1256 368000 **Sales enquiries** +44 (0)844 811 2006 **☑** info@uk.glory-global.com **♀ glory-global.com**

DS-S15-0222_1.0