

Ditron// group

www.ditron.eu



has immediate response times when disbursing change; it allows mixed payments, through EFTPOS and cash and can be conveniently used for deposits, withdrawals and exchanges. The front panel can be pleasantly



PRO



L 37cm x D 33.7cm x H 63.8 cm


Measurements are in cm + 1mm


The measurements refer only to the metal case, useful for installation operations. For a correct installation of the product it is appropriate to follow the "Installation guide".

SafeMoney Pro can be easily built into any workbench, thanks to its compact size and simple design, without making any changes.

Compared to the advance and the extreme, it features an integrated design nozzle, reducing the overall dimensions of the upper horn.









CONNESSIONS:

ETHERNET

AFFLUENCE: TTTTTT



Front door for maintenance with security lock

2 cashbox for coins and notes storage

Design "easy clean"

Increase the hygiene of the point of sale

Light feedback

Customizable front panel

Partially and totally integrable

Mast plate predisposition

Integrated UPS to guarantee completion of ongoing operations

Integrated Web service





	TECHNICAL FEATURES	EASY	SMART	PRO	ADVANCE	EXTREME
COIN RECYCLE	MAXIMUM INSERTION SPEED	"smart coin system" up to 3 coins/sec. "smart coin system" up to 10 coins/sec.				
	ACCEPTED COINS	from € 0,01 to € 2,00				
	MAXIMUM DELIVERY SPEED	up to 12 coins /sec.				
	CAPACITY IN RECYCLE	1500 coins				3600 coins
Ö	CASHBOX FOR COIN STORAGE	1.9L				X
BANKNOTES RECYCLE	INSERTION	one by one				
	ACCEPTED BANKNOTES	from € 5.00 to € 500.00				
	MAXIMUM DELIVERY SPEED	1 banknotes/ 3 sec.		1 banknotes/ 2 sec.	up to 15 banknotes simultaneously (bulknote) 1 banknote / sec.	
	CAPACITY IN RECYCLE	up to 70 banknotes		up to 120 banknotes	up to 180 banknotes	
BAN	CASHBOX	up to 500 k	0 banknotes up to 600 banknotes			otes
GENERAL FEATURES	OPERATOR DISPLAY	X		10" graphic touchscreen rotation 30°		
	CONNECTIONS	USB	ethernet			
	POWER SUPPLY	500W/100-240 VAC 50/60HZ	500W/100-240 VAC - 50/60Hz, backup power supply per chiusura transizione			
	CASE	color: black		color: white		
	DIMENSIONS (CM)	L36.5xD38xH55.8		L37xD33.7xH63.8	L41.6xD37.3xH68.5	L56xD46.8xH59.5
	WEIGHT (KG) EMPTY	35	37	40	70	80
FUNCTIONS	TOUCHSCREEN	X	✓	✓	✓	✓
	MULTIPLE INSTALLATION MANAGEMENT	X	✓	✓	✓	✓
	DIRECT INTEGRATION WITH RT DITRON	X	✓	✓	✓	✓
COMMUNICATION	REMOTE DIAGNOSTICS	X	✓	✓	✓	✓
	REMOTE SOFTWARE UPDATE	X	✓	✓	✓	✓
	UNIVERSAL COMMUNICA- TION DRIVERS ON BOARD (WEB SERVICES)	X	✓	✓	✓	✓
	UNIVERSAL COMMUNICA- TION DRIVER FOR PC	✓	✓	✓	✓	✓
	ACCESS VIA TABLET OR PC	X	✓	✓	✓	✓
OPTIONALS	INTEGRATED FISCAL PRINTER	✓	✓		X	
	INSTALLATION PLATE	predisposition				
OPT	CUSTOMIZABLE FRONT PANEL	√ (min. 4 Pz.)				

^{*}Technical specifications are subject to change without notice ** The images of the products are purely indicative

Always at the point of sale with high-tech solutions, **Ditron is the answer that helps you to enhance your business.** Your store can be supported by cutting-edge technology and your work is simplified by solutions that **speed up the cash point procedures.**













